


F22直架
STRAIGHT SEGMENT



产品描述 Description



插销式桁架F22系列

Spigot Truss F22 Series

主管: 35x2mm(1.4x0.08 inch)

斜管: $\Phi 8$ mm(0.3 inch)

铝合金: EN-AW 6082 T6

Main tube: 35x2mm(1.4x0.08 inch)

Braces: $\Phi 8$ mm(0.3 inch)

Alloy: EN-AW 6082 T6


产品描述 Description	产品型号 Item Number	长度 Length	重量 Weight	规格 Specification	包装尺寸 Package(LxWxHcm)
		m	kgs	mm	
F22直架 STRAIGHT SEGMENT	F22-50	0.5	0.96	220	23x8x50
	F22-100	1	1.61	220	23x8x100
	F22-150	1.5	2.27	220	23x8x150
	F22-200	2	2.95	220	23x8x200
	F22-250	2.5	3.61	220	23x8x250
	F22-300	3	4.27	220	23x8x300
	F22-350	3.5	4.96	220	23x8x350
	F22-400	4	5.59	220	23x8x400

承载表 LOADING TABLE

Span(m)跨度	2m	3m	4m	6m	8m	10m
Distrib.Load(kg/m)每米均布承重	101	67	48	21	11	7
Deflection(mm)变形量	0.9	2.9	6.6	15.5	27.7	43.6
Point Load(kg)中心点载	196	129	96	63	44	33
Deflection(mm)变形量	1.3	3	5.4	12.6	22.9	36.7



F22-C19-H



F22-C19-V



F22-T35-V

长度(L)	1m (3.28ft)
角度(A)	2-way 45° corner horizontal
重量(W)	1.6kgs(3.53lbs)

长度(L)	1m (3.28ft)
角度(A)	2-way 45° corner vertical
重量(W)	2.1kgs(4.63lbs)

长度(L)	0.5m (1.64ft)
角度(A)	3-way vertical T-junction
重量(W)	1.2kgs(2.65lbs)