

HT32直架
STRAIGHT SEGMENT

产品描述 Description



含插销套件
Connectors included

插销式桁架HT32系列 Spigot Truss HT32 Series

主管: 50x3mm(2x0.12 inch)

斜管: 20x2mm(0.8x0.08 inch)

铝合金: EN-AW 6082 T6

Main tube: 50x3mm(2x0.12 inch)


Braces: 20x2mm(0.8x0.08 inch)

Alloy: EN-AW 6082 T6

产品描述 Description	产品型号 Item Number	长度 Length	重量 Weight	规格 Specification	包装尺寸 Package(LxWxHcm)
		m	kgs	mm	
HT32直架 STRAIGHT SEGMENT	HT32-50	0.5	2.9	290	30x13x55
	HT32-100	1	4.29	290	30x13x105
	HT32-150	1.5	5.29	290	30x13x155
	HT32-200	2	6.73	290	30x13x205
	HT32-250	2.5	8	290	30x13x255
	HT32-300	3	9.28	290	30x13x305
	HT32-350	3.5	10.16	290	30x13x355
	HT32-400	4	11.44	290	30x13x405
	HT32-450	4.5	12.64	290	30x13x455
	HT32-500	5	13.34	290	30x13x505

承载表 LOADING TABLE

Span(m)跨度	2m	4m	6m	8m	10m	12m
Distrib.Load(kg/m)每米均布承重	710	254	115	64	40	27
Deflection(mm)变形量	1.7	9.6	22.3	40.4	64.2	94.1
Point Load(kg)中心点载	1027	508	344	256	202	165
Deflection(mm)变形量	1.9	7.7	18	32.8	52.5	77.5



HT32-C19-H

长度(L)	1m (3.28ft)
角度(A)	2-way 45° corner horizontal
重量(W)	4.2kgs(9.26lbs)



HT32-C19-V

长度(L)	1m (3.28ft)
角度(A)	2-way 45° corner vertical
重量(W)	4.9kgs(10.80lbs)



HT32-CH

长度(L)	Circle horizontal
角度(A)	Various diameters