


HT42直架
STRAIGHT SEGMENT



产品描述 Description



插销式桁架HT42系列 Spigot Truss HT42 Series

主管: 50x3mm(2x0.12 inch)

斜管: 25x3mm(1x0.12 inch)

铝合金: EN-AW 6082 T6

Main tube: 50x3mm(2x0.12 inch)


Braces: 25x3mm(1x0.12 inch)

Alloy: EN-AW 6082 T6

产品描述 Description	产品型号 Item Number	长度 Length	重量 Weight	规格 Specification	包装尺寸 Package(LxWxHcm)
		m	kgs	mm	
HT42直架 STRAIGHT SEGMENT	HT42-50	0.5	2.6	400	41x13x50
	HT42-100	1	4.1	400	41x13x100
	HT42-150	1.5	5.5	400	41x13x150
	HT42-200	2	7	400	41x13x200
	HT42-250	2.5	8.4	400	41x13x250
	HT42-300	3	9.8	400	41x13x300
	HT42-350	3.5	11.3	400	41x13x350
	HT42-400	4	12.7	400	41x13x400
	HT42-450	4.5	14.1	400	41x13x450
	HT42-500	5	15.4	400	41x13x500

承载表 LOADING TABLE

Span(m)跨度	2m	4m	6m	8m	10m	12m	14m	16m
Distrib.Load(kg/m)每米均布承重	1042	332	153	87	57	40	29	21
Deflection(mm)变形量	1.1	5.9	14	25.7	42.1	63.5	87.9	115.2
Point Load(kg)中心点载	1042	664	459	349	286	243	204	172
Deflection(mm)变形量	0.9	4.7	11.3	20.8	34.3	52	72.5	95.9



HT42-C21-V

长度(L)	0.5m (1.64ft)
角度(A)	2-way 90° corner vertical
重量(W)	3.5kgs(7.72lbs)



HT42-C22-V

长度(L)	0.5m (1.64ft)
角度(A)	2-way 120° corner vertical
重量(W)	3.5kgs(7.72lbs)