

F24
STRAIGHT SEGMENT



产品描述 Description

插销式桁架F24系列

Spigot Truss F24 Series

主管: 35x2mm(1.4x0.08 inch)

斜管: $\Phi 8$ mm(0.3 inch)

铝合金: EN-AW 6082 T6

Main tube: 35x2mm(1.4x0.08 inch)


Braces: $\Phi 8$ mm(0.3 inch)

Alloy: EN-AW 6082 T6

产品描述 Description	产品型号 Item Number	长度 Length	重量 Weight	规格 Specification	包装尺寸 Package(LxWxHcm)
		m	kgs	mm	
F24直架 BOX STRAIGHT SEGMENT	F24-50	0.5	2.62	220x220	23x23x50
	F24-100	1	4.14	220x220	23x23x100
	F24-150	1.5	5.76	220x220	23x23x150
	F24-200	2	7.26	220x220	23x23x200
	F24-250	2.5	8.70	220x220	23x23x250
	F24-300	3	10.38	220x220	23x23x300
	F24-350	3.5	12.00	220x220	23x23x350


承载表 LOADING TABLE

Span(m)跨度	2m	3m	4m	6m	8m	10m
Distrib.Load(kg/m)每米均布承重	202	134	100	65	35	21
Deflection(mm)变形量	0.9	2.9	6.9	23.1	41.3	64.8
Point Load(kg)中心点载	405	354	286	195	141	107
Deflection(mm)变形量	1.4	4.1	7.9	18.7	33.7	53.6



F24-C21

长度(L)	0.5m (1.64ft)
角度(A)	2-way 90° corner
重量(W)	2.1kgs(4.63lbs)



F24-T35

长度(L)	0.5m (1.64ft)
角度(A)	3-way T-junction
重量(W)	2.7kgs(5.95lbs)



F24-MCB

长度(L)	0.22m (0.72ft)
角度(A)	Universal junction box
重量(W)	3.5kgs(7.7lbs)